

W1B1664



16GA Brad Nailer

Applications

Cabinet Assembly, Door & Window Manufacturing,
Drawer Assembly, Finish Carpentry, Furniture Assembly,
Hardwood Flooring, Trim Molding

HOLDS 3 STRIPS OF BRADS



Specifications

Fastener Length	3/4" - 2-1/2"
Magazine Capacity	150
Actuation Mode	Selective Actuation
Dimensions	15-1/2" x 2-3/4" x 10-1/2"
Weight	3.5 lbs
Operating Pressure	80-110 PSI
Air Inlet NPT	1/4"
Air Consumption per Cycle @ 90 PSI	0.035 SCF
Noise Power Emissions per EN12549 LwA,1s	108.6 dBA
Noise Pressure Emissions per EN12549 LpA,1s	106.1 dBA
Vibration Emissions per ISO-8662-11	3.48 m/s ²
Vibration Value Uncertainty per ISO-8662-11	1.50 m/s ²

Features

360° Adjustable Exhaust, Adjustable Depth Control,
Ergonomic Rubber Grip, Heavy Duty, No Mar Tip,
Quick Clear Nose, Rear Load Aluminum Magazine

Includes

Allen Wrenches, Safety Glasses, Tool Case, Tool Oil

Accessory

Full Sequential Actuation Trigger (AS-21040)

For Best Results, Use Spotnails® Collated Fasteners

16GA Brads

STOCK No.	LENGTH	M/BX	BX/Cs	STOCK No.	LENGTH	M/BX	BX/Cs
5M Bxs - Galvanized				2.5M Bxs - 316 Stainless Steel			
16512	3/4"	5	6	16224SS-316	1-1/2"	2.5	10
16516	1"	5	6	16232SS-316	2"	2.5	10
16520	1-1/4"	5	6	16240SS-316	2-1/2"	2.5	10
16524	1-1/2"	5	6	1M Clamshell Pack - Galvanized			
16528	1-3/4"	5	6	16124	1-1/2"	1	8
16532	2"	5	4	16132	2"	1	8
16536	2-1/4"	5	4	16140	2-1/2"	1	8
16540	2-1/2"	5	4	1M Clamshell Pack - 304 Stainless Steel			
2.5M Bxs - Galvanized				16124SS-8M	1-1/2"	1	8
16220	1-1/4"	2.5	10	16132SS-8M	2"	1	8
16224	1-1/2"	2.5	10	16140SS-8M	2-1/2"	1	8
16228	1-3/4"	2.5	10	1M Clamshell Pack - 316 Stainless Steel			
16232	2"	2.5	10	16124SS-8M-316	1-1/2"	1	8
16236	2-1/4"	2.5	10	16132SS-8M-316	2"	1	8
16240	2-1/2"	2.5	10	16140SS-8M-316	2-1/2"	1	8
2.5M Bxs - 304 Stainless Steel							
16224SS	1-1/2"	2.5	10				
16232SS	2"	2.5	10				
16240SS	2-1/2"	2.5	10				



Jan. 2022